

Rust Finish

product data sheet

Location = Interior/Exterior

Use Murobond Rust Base before using Murobond Rust Finish. Customers are advised to test the product on the area to be painted prior to commencement of a project. Murobond Rust Finish gives a general rust effect similar to a rusting metal sheet.

Surface Preparation

- Prepared under application of Murobond Rust Base.

Application

- Stir well before use.
- Covers approximately 11–12m² per litre.
- Brush on freshly applied (just dry) Murobond Rust Base.
- Water may be sprayed on after Murobond Rust Finish dries to enhance the effect.

Important

- Murobond Rust Paint will continue to change and rust with exposure to weather.
- To accelerate the desired effect, lightly spray water onto the surface over 2 – 3 days or brush/roll additional coats of Murobond Rust Finish.
- Once the desired effect is achieved, or after 3 days, one coat of Murobond Rust Clear may be applied to prevent further deterioration or oxidation.
- Surface should be kept wet with Murobond Rust Finish for as long as possible to maximise effect. Cover with plastic sheeting to retain moisture if necessary, especially in hot, or dry conditions.
- Do not apply in direct sunlight or in windy conditions as Murobond Rust Finish may dry too quickly without time to react – so visible rusting will not occur.

Safety

- Keep out of reach of children.
- Provide adequate ventilation.
- WEAR SAFETY GLASSES and RUBBER GLOVES during application.
- Avoid contact with eyes and skin.
- If product causes skin irritation, gets into eyes or is swallowed seek immediate medical attention.

Environmental Protection

- Do not tip unused paint or washings down drains.
- Dispose of via special collection service.

For detailed information refer to current Product Information Sheets and Material Safety Data Sheets supplied by Murobond Coatings. We are able to recommend applicators. The information supplied is given in good faith. There are no implied conditions or warranties in the supply of this product.

Rust Base

product data sheet

Location = Interior/Exterior

Murobond Rust Paint is suitable for most interior and exterior surfaces.

Dramatic rustic finishes may be achieved through using Murobond's simple three step process.

Customers should test the product on the area to be painted before commencement of a project.

Murobond Rust Paint is not recommended for areas where water pools or ponds, or for steel surfaces externally.

- This product contains active rust which will promote rusting of steel substrates. Rust leaching may cause staining on adjacent surfaces.
- Brush or roller application.
- Covers approximately 3–4m² per litre depending on application and surface roughness.
- Do not apply if temperature is below 10°C.
- WEAR SAFETY GLASSES and RUBBER GLOVES during application.

Surface Preparation

- All surfaces must be prepared in accordance with proper trade practises.
- Remove all loose and flaking paint.
- Surfaces should be clean and free from dust.
- Undercoat prepared surfaces with Murobond Acrylic Primer.

Application

- Stir well before use.
- Brush or roll first coat generously and allow 3-6 hours to dry in normal conditions (25°C) and 50% relative humidity, dependent on conditions.
- Apply second coat as first, but only allow to partially dry (sufficient that Rust Finish can be applied without removing the base coat), typically less than 30 minutes.

Then apply Murobond Rust Finish.

Safety

- Keep out of reach of children.
- Provide adequate ventilation.
- WEAR SAFETY GLASSES and RUBBER GLOVES.
- Avoid contact with eyes and skin.
- If product causes skin irritation, gets into eyes or is swallowed seek immediate medical attention.

Environmental Protection

- Do not tip unused paint or washings down drains.
- Dispose of via special collection service.

For detailed information refer to current Product Information Sheets and Material Safety Data Sheets supplied by Murobond Coatings. We are able to recommend applicators.

The information supplied is given in good faith. There are no implied conditions or warranties in the supply of this product.